

the aforementioned details are available to each officer and a copy is retained on board at all times and is accessible during emergencies. For vessels constructed on or after September 30, 1997 or for existing vessels which have their plans redrawn, the symbols used to identify the aforementioned details shall be in accordance with IMO Assembly resolution A.654(16). These identical symbols can also be found in ASTM Adjunct F 1626.

(b) Plans showing clearly for each deck and hold the boundaries of the watertight compartments, the openings therein with the means of closure and position of any controls thereof, and the arrangements for the correction of any list due to flooding.

(c) The aforementioned information shall be kept up-to-date, any alteration being recorded in the applicable medium as soon as practicable.

[CGD 95-028, 62 FR 51207, Sept. 30, 1997]

EFFECTIVE DATE NOTE: By CGD 95-028, 62 FR 51207, Sept. 30, 1997, § 97.36-1 was revised, effective Oct. 30, 1997. For the convenience of the user, the superseded text is set forth as follows:

**§ 97.36-1 When required.**

(a) Barges with sleeping accommodations for more than six persons and all self-propelled vessels shall have permanently exhibited for the guidance of the officer in charge of the vessel, general arrangement plans showing for each deck the various fire-retardant bulkheads together with particulars of the fire detecting, manual alarm and fire extinguishing systems, fire doors, means of ingress to the different compartments, and the ventilating systems including the positions of the dampers, the location of the remote means of stopping the fans, and the identification of the fans serving each section. If cargo compartments are "specially suitable for vehicles," they shall be so indicated on the plan.

[CGFR 66-33, 31 FR 15286, Dec. 6, 1966]

**Subpart 97.37—Markings for Fire and Emergency Equipment, Etc.**

**§ 97.37-1 Application.**

(a) The provisions of this subpart, with the exception of § 97.37-90, shall apply to all vessels contracted for on or after November 19, 1952. Vessels contracted for prior to November 19, 1952,

shall meet the requirements of § 97.37-90.

**§ 97.37-3 General.**

(a) It is the intent of this subpart to provide such markings as are necessary for the guidance of the person on board in case of an emergency. In any specific case, and particularly on small vessels, where it can be shown to the satisfaction of the Officer in Charge, Marine Inspection, that the prescribed markings are unnecessary for the guidance of the persons on board in case of emergency, such markings may be modified or omitted.

(b) In addition to English, all state-room notices, directional signs, etc., shall be printed in languages appropriate to the service of the vessel or other action be taken to achieve the same purpose.

(c) Where in this subpart red letters are specified, letters of a contrasting color on a red background will be accepted.

**§ 97.37-5 General alarm bell contact maker.**

Each general alarm contact maker must be marked in accordance with requirements in subchapter J (Electrical Engineering Regulations) of this chapter.

[CGD 74-125A, 47 FR 15232, Apr. 8, 1982]

**§ 97.37-7 General alarm bells.**

(a) All general alarm bells shall be identified by red lettering at least ½ inch high:

"GENERAL ALARM—WHEN BELL RINGS GO TO YOUR STATION."

(b) [Reserved]

**§ 97.37-9 Carbon dioxide alarm.**

(a) All carbon dioxide alarms shall be conspicuously identified:

"WHEN ALARM SOUNDS—VACATE AT ONCE. CARBON DIOXIDE BEING RELEASED."

(b) [Reserved]

**§ 97.37-10 Fire extinguishing system branch lines.**

(a) The branch line valves of all fire extinguishing systems shall be plainly and permanently marked indicating the spaces served.